

MONROE CIVIC CENTER ARENA

Technical Specifications Package: Updated February 04, 2005

Number Of Seats:

	Upper Bowl	Permanent:	4,712
		Temporary:	2,688
TOTALS:	STANDARD CONCERT (Without East End Seating):		5,600
	FULL BUILDING (In Round):		7,400

MAXIMUM ARENA FLOOR WIDTH: 106'

MAXIMUM ARENA FLOOR DEPTH: 230'

GREATEST DISTANCE FROM STAGE: 180'

STAGE DIMENSIONS AND TYPE (MAX): 60' WIDE X 40' DEEP.

SICO STAGING. 4' TO 6' HIGH.

STEP UNITS: UP TO 4.

SOUND WING DIMENSIONS (MAX): 16' X 16'

BARRICADES: BICYCLE TYPE

LOADING DOCK: SPACE FOR 2 TRUCKS AT GROUND HEIGHT . LOADS DIRECTLY INTO UPSTAGE AREA ON THE EAST END OF THE BUILDING.

LOADING DOOR: 16' HIGH X 25' WIDE.

DRESSING ROOMS: (1) STAR UPSTAGE LEFT 2 - 4 PERSONS 10' X 13'

(1) CHORUS UPSTAGE LEFT 25 - 30 PERSONS 23' X 6'

(2) STAR UPSTAGE RIGHT 2 - 4 PERSONS 12' X 12'

(2) CHORUS UPSTAGE RIGHT 25 - 30 PERSONS 23' X 26'

ALL DRESSING ROOMS HAVE TOILETS, SINKS, SHOWERS. SOME HAVE LIGHTED MAKE UP TABLES WITH MIRRORS, RACKS AND CHAIRS.

PROMOTER'S/ PRODUCTION OFFICE: UPSTAGE LEFT BY LOADING DOOR. PHONE LINES AVAILABLE.

ADDITIONAL MEETING ROOMS: VIP ROOM (SOUTH CONCOURSE) 25' X 32'

RIGGING : MUST BE RIGGED USING EYEBOLTS THROUGH SUPPORT BEAMS OR WITH BEAM CLAMPS. MAXIMUM 1700 LBS. PER EYEBOLT. A RIGGING TRUCK IS REQUIRED FOR ANY RIGGING OUTSIDE OF THE CENTER CATWALK. (REQUIRED FOR MOST EVENTS.)

NUMBER OF POINTS: THIS IS DEPENDENT ON STAGE LOCATION. UP TO 60 POINTS.

HEIGHT: TO CATWALK: 58'

TO MAXIMUM CEILING: 72'

POWER: (EAST WALL BY LOADING DOOR) WITHIN 100' OF STAGE:

- (2) 200 AMP 3 PHASE 120/208 VOLT
- (1) 400 AMP 3 PHASE 120/208 VOLT
- (2) 600 AMP 3 PHASE 120/208 VOLT

HOUSE LIGHTING SYSTEM: – 9 TRUSSES WITH 5 METAL HALIDE AND 2 FLORESCENT FIXTURES EACH. AVERAGE INTENSITY IS 80 FOOTCANDLES. WHEN COLD, THE METAL HALIDE FIXTURES REQUIRE 5 MINUTES TO REACH FULL INTENSITY. WHEN HOT, AFTER BEING TURNED OFF, THE METAL HALIDE FIXTURES REQUIRE A 20 MINUTE COOL DOWN PERIOD BEFORE THEY WILL RESTRIKE.

CONTROL IS FROM THE EAST END OF THE BUILDING OR FROM THE SOUND BOOTH ON THE SOUTH SIDE OF THE ARENA.

FOLLOW SPOTLIGHTS: (4) STRONG XENON 2000 WATT SUPER TROOPERS. (2) WEST END, (1) NORTH, (1) SOUTH.

COMMUNICATIONS, SOUND AND VIDEO EQUIPMENT:

INTERCOM: CLEAR COM CS - 222 2 CHANNEL MASTER STATION LOCATED IN THE SOUND BOOTH. A PATCH BAY IS IN PLACE TO PATCH EITHER CHANNEL OF INTERCOM TO VIRTUALLY ANY POINT ON THE ARENA FLOOR, CATWALK OR SPOT PLATFORM. DRY PATCHING IS AVAILABLE FOR USING SHOW PROVIDED MASTER STATIONS. (12) HEADSETS AND BELT PACKS AVAILABLE.

IN HOUSE SOUND SYSTEM:

- (1) ALLEN AND HEATH MIX WIZARD 14 CHANNEL CONSOLE LOCATED IN THE SOUTH SOUND BOOTH WITH DUAL CD PLAYER, CASSETTE, AND FM TUNER. UP TO 3 MICROPHONES MAY BE USED WITH THIS SYSTEM WITHOUT THE NEED FOR AN EXTERNAL MIXER. INPUTS AND OUTPUTS MAY BE PATCHED FROM/TO LOCATIONS ON THE ARENA FLOOR.
- (2) SOUND COVERAGE IS PROVIDED BY A CENTRAL CLUSTER WITH PEAVEY COMPONENTS AND A DELAY CLUSTER OF EV SX – 300'S TO SUPPLEMENT THE WEST END COVERAGE. ADDITIONAL CEILING SPEAKERS COVER THE CONCOURSE AND SOME DRESSING ROOMS.
- (3) THE SYSTEM IS SUITABLE FOR VOICE AND MODERATE MUSIC.

VIDEO SYSTEM:

VIDEO SIGNALS MAY BE TRANSMITTED TO 6 MONITORS PLACED ON THE CONCOURSE AND THE LOBBY. SIGNALS ORIGINATE FROM THE SOUTH SOUND BOOTH.

SCOREBOARD: A DAKTRONICS CENTER HUNG AND END ZONE SCORING SYSTEM IS IN PLACE. CONTROL MAY BE OPERATED FROM THE NORTH OR SOUTH SIDE OF THE ARENA FLOOR. WRESTLING /BOXING LIGHTS ARE MOUNTED UNDER THE CENTER HUNG SCOREBOARD AND ARE CONTROLLED FROM THE SOUTH SOUND BOOTH. THE CENTER HUNG SCOREBOARD MAY BE ADJUSTED IN HEIGHT , BUT IS NOT REMOVEABLE. THE SYSTEM IS SUITABLE FOR INDOOR FOOTBALL, HOCKEY OR BASKETBALL.

BASKETBALL FLOOR: REGULATION SIZE HARDWOOD FLOOR AVAILABLE WITH 2 HYDRARIB GOALS.

TRADE SHOWS: 44,000 SQUARE FEET OF EXHIBIT SPACE WITH CURTAINS AND POLES.

UP TO 175 BOOTHS ON THE ARENA FLOOR. MORE MAY BE PLACED ON THE CONCOURSES.

INDIVIDUAL 120 VOLT RECEPTACLE S AVAILABLE FOR BOOTHS.

SINGLE PHASE 208 VOLT OR THREE PHASE 120/208 VOLT AVAILABLE UPON SPECIAL REQUEST.

TELEPHONE SERVICE AVAILABLE BY REQUEST.

FORKLIFT: 6000 LB. CAPACITY AVAILABLE WITH EXTENSIONS UPON REQUEST.

REFER TO GROUND PLAN FOR MORE INFORMATION.